DARMOSHARK

KT35 Wired Magnetic Switch Keyboard

QUICK START GUIDE

Darmoshark

简体中文

FN+ESC=长按5秒恢复出厂设置

FN+5%=PGUP

FN+6^ =PGDN

FN+backspace=开/关背光灯

FN+T=INS

FN+Y=DEL

FN+\|=HOME

FN+G=END

FN+Z=灯效模式切换（23种）

FN+X=灯效单色切换

FN+C=灯效方向切换（个别模式）

FN+V=五级亮度调节

FN+B=五级速度调节

系统支持

WINXP/WIN7/WIN8/WIN10/WIN11

中文
尺寸:188×110×38.61mm
重量:685±10G
寿命:1亿次
数量:35键

English
Size:188×110×38.61mm
Weight:685±10G
Life:100,000,000 times
Quantity: 35 keys

Español
Tamaño: 188×110×38.61mm
Peso: 685±10G
Vida: 100,000,000 veces
Cantidad: 35 llaves

Türk dili
Boyut: 188×110×38.61mm
Ağırlık: 685±10G
Hayat:100,000,000 kez
Miktar:35 tuş

Português
Tamanho: 188×110×38.61mm
Peso:685±10G
Vida: 100,000,000 vezes
Quantidade: 35 chaves

Українська
Розмір: 188×110×38.61mm
Вага: 685±10G
Життя:100,000,000 разів (рази)
Кількість: 35 ключів

Ελληνικά
Μέγεθος:188×110×38.61mm
Βάρος:685±10G
Ζωή: 100,000,000 φορές
Ποσότητα:35κλειδιά

Deutsch
Größe:188×110×38.61mm
Gewicht:685±10G
Leben:100,000,000 mal
Menge: 35 Schlüssel

Polski
Rozmiar: 188×110×38.61mm
Waga:685±10G
Życie:100,000,000 razy
Ilość: 35 klawiszy

规格参数

铝合金底+铭牌LOGO：CNC工艺

磁轴品牌：RAESHA磁轴

操作寿命：1亿次（正常使用）

初始力度：35±10G

触底力度：50±10G

初始磁通量：75±15GS

触底磁通量：580±80GS

按压行程：4.0±0.4MM

灵敏度：可通过驱动设置按键精度（0.01–2.2MM）0死区

触发行程：可通过驱动设置按键行程（0.1–4.0MM）

回报率：8Khz

方案特点及硬件规格

1. 高性能CPU芯片32位，支持浮点运算，DSP指令；高效运行算法代码；超100M主频，超高主频；
2. 高速USB 2.0 High speed，8K轮询率；0.125MS低延时；
3. 8K全键按键扫描率，0.08ms极致延时；
4. 自研磁轴检测算法，高效稳定；支持混轴，动态校准;
5. 自动校准算法，补偿温差带来的影响；
6. 深度优化的电源设计，抗干扰性强；
7. 独立RGB灯光芯片，1600万色；

字键数量

35键 支持全键无冲

键盘类型

高键帽阶梯设计

工作电流

最大250MA

工作电压

DC5V±5%

大小写指示灯

短按CAPS键，对应键下的灯来提示工作状态
(打开功能此灯混白光常亮，关闭功能此灯参与当前灯效)

键盘无法工作及故障排除

1. 检查USB连接线是否妥当连接在电脑上。
2. 试着将键盘连接至电脑的其它USB端口。
3. 尝试将电脑重新开机。
4. 若仍然无法工作，试着将键盘连接到其他电脑上

保修说明

请妥善保留此保修卡及有效购买凭证，于产品故障送修时一并出示，或您无法提供保修卡（需加盖经销商有效公章）或相关购买凭证，则产品保修期起算日将以产品上的出厂日期为准。

服务条例

1. 质保服务：产品自出售之日起，在正常使用情况下，若产品出现品质故障用户可以在购买七天内申请退货，一年内提供保修服务。若属于下列原因,恕不提供保修服务：

   1. 不能出示有效保修卡原件和有效发票或收据，或者机身条码、保修日期贴纸撕毁或损坏。
   2. 购买产品日期、销售单位名称（盖章有效）等项目未能完整填写或涂改保修卡。
   3. 一切人为因素损坏、包括非正常工作环境下使用所导致的故障和损坏。
   4. 未经许可对产品进行改造、分解、组装或维修而发生的故障。
   5. 产品缺少配件，如无产品质保贴及其他相关配件。
   6. 除正常使用所产品的电器性能故障外，如果外观损坏，只能享受维修服务。

保修凭证

顾客姓名：_____ 购买型号：_____

电话或地址：_____

经销商（签章）：_____

维修记录：_____

_____

Mototech Technology Group Limited
Add:Xinqiao Chuanggu Industrial Area, Bao'an, Shenzhen, China
飞翔科技集团有限公司
地址:深圳市宝安区新桥创谷科技园
www.darmoshark.com
www.darmoshark.cn
Made in China
HOTLINE: 4008-860-368

以上数据仅供参考，实物与图片可能不相符！
最终解释权归本公司所有

English

FN+ESC=Press and hold for 5 seconds to restore factory settings

FN+5%=Page Up

FN+6^ =Page Down

FN+Backspace=Backlight on/off

FN+T=Insert

FN+Y=Delete

FN+\|=Home

FN+G=End

FN+Z=Light effect mode switch (23 modes)

FN+X=Switch to single-color lighting effect

FN+C=Switch lighting direction (select modes)

FN+V=Adjust brightness in 5 levels

FN+B=Adjust speed in 5 levels

Size: 188×110×38.61mm
Weight:685±10G
Life:100,000,000 times
Quantity: 35 keys

SYSTEM SUPPORT

WINXP/WIN7/WIN8/WIN10/WIN11

SPECIFICATION

Aluminium alloy bottom + nameplate LOGO: CNC process

Magnetic shaft brand: RAESHA magnetic shaft

Operating life: 100 million times (normal use)

Initial strength: 35±10G

Touchdown force: 50±10G

Initial magnetic flux: 75±15GS

Bottom flux: 580±80GS

Press stroke: 4.0±0.4MM

Sensitivity: can be set by the driver key precision (0.01–2.2MM) 0 dead zone

Trigger stroke: can be set by the driver key stroke (0.1–4.0MM)

Return rate: 8kHz

PROGRAMME FEATURES AND HARDWARE SPECIFICATIONS

1. High–performance CPU chip 32–bit, support for floating point operations, DSP instructions; efficient operation of the algorithm code;
Super 100M main frequency, ultra–high main frequency;
2. High–speed USB 2.0 High speed, 8K polling rate; 0.125MS low latency;
3. 8K full key scanning rate, 0.08ms extreme delay;
4. self–developed magnetic axis detection algorithm, efficient and stable; support for mixed axis, dynamic calibration.
5. Automatic calibration algorithm to compensate for the impact of temperature difference;
6. deeply optimised power supply design, strong anti–interference;
7. Independent RGB lighting chip, 16 million colours;

NUMBER OF KEYS

35 keys Support all keys without punch

KEYBOARD TYPE

High keycap step design

OPERATING CURRENT

Maximum 250MA

INDICATOR LIGHT

Short press the CAPS key, corresponding to the light under the key to indicate the working state
(Turn on the function of this light mixed white light is always on, turn off the function of this light to participate in the current light effect)

KEYBOARD NOT WORKING AND TROUBLESHOOTING

1. Check that the USB cable is properly connected to the computer.
2. Try connecting the keyboard to another USB port on the computer.
3. Try turning the computer back on.
4. If it still does not work, try connecting the keyboard to another computer

WARRANTY CARD DESCRIPTION

Please keep this warranty card and valid proof of purchase and present it when the product is sent for repair, or if you cannot provide the warranty card (which must be stamped with the dealer's official seal) or relevant proof of purchase, the starting date of the product warranty period will be based on the date of shipment of the product.

SERVICE REGULATION

1. Warranty service: products from the date of sale, under normal use, if the product quality failure users can apply for return within seven days of purchase, within one year to provide warranty service. If belong to the following reasons, will not provide warranty service:

1. Failure to present the original valid warranty card and a valid invoice or receipt, or the body barcode, warranty date sticker torn or damaged.
2. Failure to fill in the warranty card completely or alteration of the warranty card, such as the date of purchase of the product, the name of the sales unit (stamped validity and other items).
3. All human factors damage, including failure and damage caused by the use of non-normal working conditions. 4 unauthorised modification of the product, decomposition, assembly or maintenance and failure to occur
5. The product lacks accessories, such as no product warranty stickers and other related accessories.
6. In addition to the normal use of the product's electrical performance failures, if the appearance of damage, can only enjoy repair services.

WARRANTY CERTIFICATE

Customer Name: _____ Purchase Model: _____

Phone number or address: _____

Dealer (signed): _____

Maintenance records: _____

_____

Mototech Technology Group Limited
Add:Xinqiao Chuanggu Industrial Area, Bao'an, Shenzhen, China
www.darmoshark.com
www.darmoshark.cn
Made in China
HOTLINE: 4008-860-368

The above data is for reference only, the physical and the picture may not match! The final interpretation right belongs to the company

日本語

FN+ESC=長押し5秒で工場出荷時設定に復元

FN+5%=ページアップ

FN+6^ =ページダウン

FN+backspace=バックライトのオン/オフ

FN+T=INS

FN+Y=DEL

FN+\|=HOME

FN+G=END

FN+Z=ライトエフェクトモード切替（23種類）

FN+X=ライトエフェクト単色切り替え

FN+C=ライトエフェクト方向切り替え（一部モード）

FN+V=5段階輝度調節

FN+B=5段階速度調節

サイズ：188×110×38. 61㎜
重量: 685±10G
寿命: 10000万回
数量: 35キー

系统支持

WINXP/WIN7/WIN8/WIN10/WIN11

仕様

アルミニウム合金ベース+銘板ロゴ：CNC加工

磁気軸ブランド：RAESHA磁気軸

操作寿命:1億回（正常使用時）

初期力:35±10G

底面接触力:50±10G

初期磁束密度:75±15GS

底面接触磁束密度:580±80GS

押下ストローク:4.0±0.4mm

感度：ドライバー設定でキー精度（0.01~2.2mm）を調整可能 0デッドゾーン トリガーストローク：ドライバー設定でキーストローク（0.1~4.0mm）を調整可能

利回り：8kHz

プログラムの特徴とハードウェアの仕様

1. 高性能32ビットCPUチップ、浮動小数点演算およびDSP命令対応；
アルゴリズムコードの効率的な実行；
100MHzを超えるクロック周波数、超高クロック周波数；
2. 高速USB 2.0 High Speed、8Kポーリングレート；0.125msの低遅延；
3. 8K全キースキャンレート、0.08msの極限遅延；
4. 自社開発の磁気軸検出アルゴリズム、高効率で安定；混合軸対応、動的校正；
5. 自動校正アルゴリズム、温度差の影響を補償；
6. 深度最適化された電源設計、高い耐干渉性；
7. 独立したRGB照明チップ、1600万色；

キー数

35キー パンチなしの全キーをサポート

キーボードタイプ

高いキーキャップ段差デザイン

動作電流

最大250MA

動作電圧

DC5V±5%

インジケータランプ

CAPSキーを短押しすると、対応するキー下のランプが点灯し、動作状態を表示します。
（機能オン時はこのランプが白色光で常時点灯し、
機能オフ時はこのランプが現在の照明効果に参加します）

キーボードが動作しない、トラブルシューティング

1.USBケーブルがコンピュータに正しく接続されているか確認してください。

2.キーボードをコンピュータの別のUSBポートに接続してみてください。

3.コンピュータの電源を入れてみてください。

4.それでも動かない場合は、キーボードを別のコンピュータに接続してみてください。

保証規定

保証書と有効な購入証明書を紛失しないよう大切に保管してください。故障などによる修理をお受けになる場合には、保証書と購入証明書をご提示の上、修理をご依頼ください。

サービス規定

保証サービス: 本製品を正常な使用方法で故障が生じた場合には、製品販売日から起算して、15日以内の返品交換、または1年間の無償修理を申請することができます。保証期間内でも次のような場合は、交換・保証サービスの提供は無効と致します。

1. 有効な保証書と領収書・納品書をご提示いただけない場合、または購入者ではない第三者に譲渡された場合。国内モデルではない並行輸入品は対象外。
2. 製品の購入日、販売店名（購入履歴のスクリーンショット）等をご提示いただけない場合、または保証書が改ざんされている場合。
3. 異常な作業環境での使用など、人為的な要因により故障または破損した場合。
4. 製品の不正な改造、分解、組み立て、修理により故障した場合。
5. 製品保証シールなどの付属品が欠品した場合。
6. 通常の使用における製品の電気的な不具合以外、製品の外観が損傷した場合は、有償修理サービのみ利用可能です。

保証書

お客様のお名前：＿＿＿＿＿＿＿＿＿＿

電話または住所：＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿

販売店名（印）　：＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿

故障内容：＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿

＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿＿

国内総合代理店：HARUHI ハルヒ電冷株式会社
メール：support@haruhidenrei.co.jp 電話：03-6820-3737
住所: 〒103-0012 東京都中央区日本橋堀留町1-11-10
堀留ファーストビル9F
サポートホームページ: http://haruhidenrei.jp
Manufacturer: Mototech Technology Group Limited

上記のデータは参考用です。実際の製品は画像と一致しない場合があります。

www.darmoshark.com
www.darmoshark.cn